

# rsc — BiBTeX styles for Royal Society of Chemistry and Wiley journals\*

Joseph Wright<sup>†</sup>

Released 2011/01/04

## Abstract

The rsc package provides BiBTeX style files to produce bibliographies in accordance with the guidelines of the Royal Society of Chemistry and Wiley chemistry-related journals. The styles require the use of natbib. In addition, a short LATEX package is included; this provides a convenient user interface to the customisation hooks made available by the BiBTeX styles.

Contents	LATEXpackage	2
1 Introduction	1 5 Demonstration file	3
2 Installation	1 6 Change History	3
3 Using the styles	2 7 Index	3
4 Customising the styles: the	8 References	4

## 1 Introduction

Although synthetic chemists do not, in the main, use LATEX for the preparation of journal articles, it would be nice to be able to use it for reports. The package achemso provides for a BiBTeX style and other support for reports in the style of the American Chemical Society. The aim of the rsc package is to provide similar support for the style favoured by the Royal Society of Chemistry. The package also provides support for the style used in Wiley-published journals.

As of version 3, this bundle requires natbib; the package mciteplus is also supported but not required. These two packages make creating bibliographies much easier for chemists.

## 2 Installation

The entire bundle is supplied with the TDS-ready ZIP file, `rsc.tds.zip`. Simply unzip this into your local texmf tree and run your hash program (texhash for TeXLive or initexmf -u for MiKTeX).

---

\*This file describes version v3.1e, last revised 2011/01/04.

<sup>†</sup>E-mail: joseph.wright@morningstar2.co.uk

To extract the bundle of files from `rsc.dtx`, run (pdf)TeX on `rsc.dtx`. This will produce all of the package files, and also `README.txt`. To extract the files and build the documentation, run (pdf)LAT<sub>E</sub>X on `rsc.dtx`. The files can then be installed as above.

### 3 Using the styles

The styles are used in the normal way for BibT<sub>E</sub>X styles, as the argument to the `\bibliographystyle` macro. As `natbib` is required, it must of course be loaded. Citations can then be given as normal:

```
Some standard citations
  \cite{Abernethy2003,Cotton1999}.
Some \textsf{natbib}-specific features:
  \citet{Abernethy2003} have said something,
  as reported by \citeauthor{Cotton1999},
  in \citeyear{Abernethy2003}.
Some standard citations.1,2 Some natbib-specific features: Abernethy et al.1 have said
something, as reported by Cotton et al., in 2003.
```

If the `mciteplus` package is available, multiple citations can be combined into a single list:

```
A multiple citation
  \cite{Arduengo1992,*Arduengo1994}.\\
A multiple citation.3
```

To make life slightly easier for the user, a small LAT<sub>E</sub>X package accompanies the BibT<sub>E</sub>X files. It automatically loads the support packages, and handles customisation (see the next section).

```
\documentclass{article}
\usepackage{rsc}
\begin{document}
% Document body here
\bibliographystyle{rsc} % or angew
\bibliography{your-bibtex-database}
\end{document}
```

### 4 Customising the styles: the LAT<sub>E</sub>X package

Both of the styles provide a small number of control hooks to modify the output behaviour. These can be altered directly, using a mechanism similar to that used by IEEEtrans. However, for most users, this is overly complex. A short LAT<sub>E</sub>X package is therefore provided, which provides high-level access to the customisation.

`maxnames`      The `maxnames` option sets whether and when a long list of authors is truncated, and takes an integer value. Giving the value 0 means that no truncation occurs, otherwise the list is truncated if the number of names exceeds the given value. The `usetitle` and `usedoi` options are simple Boolean switches. The

`usetitle` option sets whether to include the titles of journal articles in the bibliography. The default is `false`; the only RSC journal using article titles is *Photochemical & Photobiological Sciences*. The `usedoi` option forces the use of DOI information in cases where it would not normally be present (for example journal articles with page ranges available). This is intended to make it easier for readers to find journal information. The related `linkdoi` option will include a hyperlink for each DOI, so that the DOI can be clicked on to resolve the original reference.

`super` The `super` Boolean option turns on superscript citations, and is true by default. It also causes the `natmove` package to be loaded if available (`natmove` is part of the `achemso` bundle). This ensures that citations appear *after* punctuation even if given before in the text. This documentation has been compiled using `natmove`: see the input of the example citations in the previous section.

`mciteplus` The `rsc` package normally loads the support package `mciteplus`. This can be controlled using the `mciteplus` option: loading `rsc` with `mciteplus=false` will skip loading `mciteplus`.

## 5 Demonstration file

This bundle includes the demonstration file `rsc-demo.tex`. The file shows how to create a submission to the RSC, using only standard L<sup>A</sup>T<sub>E</sub>X tools. Note that the demonstration does *not* aim to look like a published paper: this is not required for submission. The demonstration file should be installed in the `doc/latex/rsc` directory.

## 6 Change History

v1.0		v3.1	
General: Initial release of packaged		General: mciteplus package optional	1
<code>rsc.bst</code> .....	1	Demonstration file included	1
v2.0		v3.1d	
General: First re-write of package	1	General: New <code>linkdoi</code> option	1
v3.0		v3.1e	
General: Second re-write of package	1	General: Option to skip loading	
		<code>mciteplus</code>	1

## 7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

L	O		
<code>linkdoi</code> (option) .....	2	<code>options:</code>	
		<code>linkdoi</code> .....	2
		<code>maxnames</code> .....	2
		<code>mciteplus</code> .....	3
		<code>super</code> .....	3
		<code>usedoi</code> .....	2
		<code>usetitle</code> .....	2
M			
<code>maxnames</code> (option) .....	2	S	
<code>mciteplus</code> (option) .....	3	<code>super</code> (option) .....	3
		U	
		<code>usedoi</code> (option) .....	2
		<code>usetitle</code> (option) .....	2

## 8 References

- [1] C. D. Abernethy, G. M. Codd, M. D. Spicer and M. K. Taylor, *J. Am. Chem. Soc.*, 2003, **125**, 1128–1129, DOI: [10.1021/ja0276321](https://doi.org/10.1021/ja0276321).
- [2] F. A. Cotton, G. Wilkinson, C. A. Murillio and M. Bochmann, *Advanced Inorganic Chemistry*, Wiley, Chichester, 6th edn., 1999.
- [3] (a) A. J. Arduengo, III, H. V. R. Dias, R. L. Harlow and M. Kline, *J. Am. Chem. Soc.*, 1992, **114**, 5530–5534, DOI: [10.1021/ja00040a007](https://doi.org/10.1021/ja00040a007); (b) A. J. Arduengo, III, S. F. Gamper, J. C. Calabrese and F. Davidson, *J. Am. Chem. Soc.*, 1994, **116**, 4391–4394, DOI: [10.1021/ja00089a029](https://doi.org/10.1021/ja00089a029).