

The `bibexport.sh` script

Nicolas Markey

2011/11/28

Abstract

`bibexport.sh` is a small shell script, relying on Bib_{TEX}, that extracts entries of one or several `.bib` file(s). It will expand abbreviations and cross-references, except standard month and journal abbreviations. The output is indented as neatly as possible, yielding a readable `.bib` file even if the original file is not.

1 Exporting `.bib` files

1.1 Why and how?

Bib_{TEX} aims at allowing for the use of one single `.bib` file, containing many entries, from which Bib_{TEX} extracts only the `\cited` ones. When sending a document to someone else, this requires either sending the whole file, or extracting the `\cited` entries from the `.bib` file.

Bib_{TEX} also has a mechanism for using abbreviations and cross-references. When extracting entries of a large `.bib` file, it can be interesting to develop those abbreviations, in order to get a clean, self-contained `.bib` file. Also, it may be useful to develop cross-references in a `.bib` file, independently of any document.

`bibexport` can either extract entries that are cited in a document, or all the entries of one or several `.bib` files. It will always develop cross-references and abbreviations, except standard abbreviations for months or some journals, that are defined in standard Bib_{TEX} styles. This script uses Bib_{TEX}. This has both pros and cons:

- + it is very simple. Basicly, the script simply calls Bib_{TEX}, and the `.bst` file just outputs the name and the content of each field.
- + since it uses Bib_{TEX}, we are sure that it will handle everything "properly", *i.e.* in the same way as they will be handled when cited in a L^AT_EX document;
- = Bib_{TEX} has some strict limitations (especially "no more than 78 consecutive non-space characters") that we must be aware of. On the other hand, any such problem occuring within the script would also occur when compiling a document;

- abbreviations and cross-references will *always* be developed. It could be argued that this is also a positive point, but having the choice would be better.
- Many people seem to find BibTeX’s internal language clumsy, and thus the script could be difficult to adapt to special needs. However, this is not *that* difficult, as will be explained later on. In the present case, adding more fields to be exported is quite easy.

1.2 Related scripts

Several other tools exist for achieving this task:

- **aux2bib**, written by Ralf Treinen, relies on **bib2bib**, which is a CAML program for selecting some entries in one or several **.bib** files. It does not expand anything, but includes all the necessary definitions and entries.
- **bibextract.sh**, by Nelson Beebe. This script uses AWK for extracting some entries out of a **.bib** file. It is said not to be compliant with cross-references.
- **subset.bst**, by David Kotz. **export.bst** develops the same ideas (but I discovered that only later on). **subset.bst** does not handle **@preamble**, neither does it “protect” standard abbreviations.

1.3 Some examples

- extracting **\cited** references of a document, also including cross-references:

```
bibexport.sh -o <result>.bib <file>.aux
```

- extracting **\cited** references of a document, without crossrefs, and using a special **.bst** file:

```
bibexport.sh -b <style>.bst -o <result>.bib <file>.aux
```

- export all the entries of two **.bib** files (including crossrefed entries):

```
bibexport.sh -a -o <result>.bib <file1>.bib <file2>.bib
```

- export all the entries of two **.bib** files (without crossrefs):

```
bibexport.sh -a -n -o <result>.bib <file1>.bib <file2>.bib
```

In fact, the only difference between this and the previous one is that **crossref** field will be filtered out at the end of the script.

- export all the entries of two **.bib** files, using an extra file containing cross-referenced entries (which should not be included):

```
bibexport.sh -a -e <crossref>.bib -n -o <result>.bib \
<file1>.bib <file2>.bib
```

1.4 Exporting extra fields

By default, `bibexport.sh` exports only "standard" fields (those defined and used in `plain.bst`), as well as a few others. It is very easy to modify it in order to export other fields: it suffices to modify `export.bst` as follows:

- in the `ENTRY` list, add the name of the field you would like to export. Notice that `ENTRY` takes three space-separated lists as arguments; you must add extra fields in the first argument (actually, the last two are empty).
- in the function `entry.export.extra`, add a line of the form

```
"myfield" myfield field.export
```

where `myfield` is the name of the extra field you want to export.

Acknowledgements

I thank Éric Colin de Verdière, Richard Mathar, Harald Hanche-Olsen and Damien Pollet for suggesting several improvements or corrections.

2 The code

2.1 The shell script

2.1.1 Initialization

`testfiles` We check that the `.bst` files have the correct version number:

```
1 (*script)
2 function checkversion()
3 {
4   kpsewhich expcites.bst > /dev/null ||
5   echo -e "-----\n--Warning-- file expcites.bst not found.\n-----"
6   grep -q $VDATE `kpsewhich expkeys.bst` ||
7   echo -e "-----\n--Warning-- the version of the .bst files does not match with that
8 }
9 
```

`usage` We first define how the script should be used:

```
10 (*script)
11 function usage()
12 {
13 echo "bibexport: a tool to extract BibTeX entries out of .bib files.
14 usage: 'basename $0' [-h|v|n|c|a|d|s|t] [-b|e|s|e|c|o|r file] file...
15
16 Basic options:
17 -----
18 -a, --all                  export the entire .bib files
19 -o bib, --output-file bib  write output to file      [default: bibexport.bib]
```

```

20 -t, --terse          operate silently
21 -h, --help           print this message and exit
22 -v, --version        print version number and exit
23
24 Advanced options:
25 -----
26 -b bst, --bst bst   specifies the .bst style file [default: export.bst]
27 -c, --crossref       preserve crossref field [default: no]
28 -n, --no-crossref   remove crossref'd entries [default: no]
29 -e bib, --extra bib extra .bib file to be used (crossrefs and strings)
30 -es bib, --extras bib extra .bib file to be used (for strings)
31 -ec bib, --extrac bib extra .bib file to be used (for crossrefs)
32 -p, --preamble      write a preamble at beginning of output
33 -r bib, --replace bib replace .bib file(s) in the .aux file
34 -d, --debug          create intermediate files but don't run BibTeX";
35 exit 0;
36 }
37 </script>

```

opttoolate We also have a function to warn if extra options are given after the names of input files, which is not allowed.

```

38 <*script>
39 function opttoolate()
40 {
41 if [ ${TOOLATE} -ne 0 ]; then
42     echo "No option is allowed after the input files";
43     exit 0;
44 fi
45 }
46 </script>

```

VERSION We define the default value of some variables:

- VDATE** • \$VERSION: the version number;
- ALL**
- CREF** • \$VDATE: the release date;
- DEBUG**
- FILE** • \$ALL: a flag indicating that all entries of the given (.bib) file are to be exported;
- EXT**
- EXTRA**
- EXTRABIB** • \$CREF: the value of -min-crossrefs;
- REPLACEBIB** • \$FILE: the input file(s);
- NEWBIB**
- SPACE**
- BST**
- TERSE**
- BANNER**
- ARGS**
- TOOLATE** • \$EXT: the extension (.aux or .bib) of input files;
- \$EXTRA: list of possible extra .bib files without extension;
- \$EXTRABIB: list of possible extra .bib files with extension;
- \$REPLACEBIB: flag indicating that we will replace the .bib file given in the .aux file with a new one;

- \$NEWBIB: new .bib file to replace that given in the .aux file;
- \$SPACE: file name separator (can be _, comma or empty);
- \$BST: the .bst file to be used;
- \$TERSE: run silently;
- \$BANNER: don't print the initial comment;
- \$ARGS: the list of arguments passed to bibexport.sh;
- \$TOOLATE: options are not allowed once we have encountered the first non-option argument.
- \$DEBUG: create intermediate files but do not run BibTeX.

```

47 /*script)
48 ## Version number
49 VERSION="3.01";
50 ## Release date
51 VDATE="2011/11/28";
52
53 # ALL is a flag set to 1 when '-a' is given
54 ALL="0";
55 # FILE will be the main input file(s) (.aux or .bib, depending on '-a')
56 FILE="";
57 # EXT is the extension of the input file(s) (.aux, or .bib if '-a')
58 EXT=".aux";
59 # EXTRA and EXTRABIB are two copies of the extra files ('-e'), used to
60 # include crossref'd entries and @string's
61 EXTRA="";
62 EXTRABIB="";
63 # REPLACEBIB ('-r') is set to 1 when the \bibdata of the .aux input file
64 # must be ignored (then '-e' must be used)
65 REPLACEBIB="0";
66 # NEWBIB will contain the argument given to -r
67 NEWBIB="";
68 # BST is the .bst file to be used (default to export.bst)
69 BST="export";
70 # TERSE will be set to '-terse' if '-t' is given
71 TERSE="";
72 # BANNER is used to turn on or off the preamble informations in the output
73 BANNER="false";
74 # CREF is the number of citations of crossrefs from which the crossref'd entry
75 # must be included.
76 CREF="0";
77
78 # SPACE will be either ' ' or ','
79 SPACE="";
80 # TOOLATE is used to prevent extra options after the main file

```

```

81 TOOLATE="0";
82 # DEBUG is used to create files but not run BibTeX.
83 DEBUG="";
84
85 ARGS=$@;
86 </script>
```

2.1.2 Handling arguments

If no argument have been supplied, we call `usage`. Otherwise, we check version number.

```

87 <*script>
88 if [ $# -eq 0 ]; then
89   usage;
90 fi
91 checkversion;
92 </script>
```

Otherwise, we enter a `while`-loop for handling the whole list of arguments:

```

93 <*script>
94 while [ $# != 0 ]; do
95   case $1 in
96     </script>
```

- `-a` or `--all`: export all the bibliography. This means that we input `.bib` files.

```

97   <*script>
98     -a|--all)
99       ## - export all entries in the input file(s)
100      ## - the input files are BibTeX files
101      opttoolate;
102      EXT="" ; SPACE="" ; ALL=1;
103      shift ;;
104 </script>
```

- `-b` or `--bst`: specifies the style file. It seems that BibTeX does not like the `./style.bst` syntax, and we have to handle that case separately.

```

105   <*script>
106     -b|--bst)
107       ## - specifies the .bst file to use (default to 'export.bst')
108       opttoolate;
109       if [ `dirname $2` = "." ]; then
110         DOLLARTWO=`basename $2 .bst`;
111       else
112         DOLLARTWO=`dirname $2`/`basename $2 .bst`;
113       fi
114       BST="${DOLLARTWO}";
115       shift 2;;
116 </script>
```

- **-d** or **--debug**: only creates (and preserves) the intermediate files. This can help finding problems with the script or **.bst** files.

```

117      <*script>
118          -d|--debug)
119              ## - debug mode: we create files but do not run bibtex
120              ## - instead, we print what we would have done...
121                  opttoolate;
122              DEBUG="echo";
123              shift ;;
124      </script>
```

- **-e** or **--extra**: when we want to export all the entries of a **.bib** file, we can specify an extra **.bib** file that would contain entries that we don't want to export, but that are needed, *e.g.* for crossrefs.

```

125      <*script>
126          -e|--extra)
127              ## - extra input files (containing crossrefs or strings)
128              ## - they will be included twice: once before the main file(s)
129              ## (for @string's), once after (for crossrefs). We fool BibTeX
130              ## by naming the first one 'file.bib' and the second one
131              ## 'file.bib.bib', to avoid complains.
132                  opttoolate;
133                  if [ `dirname $2` = "." ]; then
134                      DOLLARTWO="`basename $2 .bib`";
135                  else
136                      DOLLARTWO="`dirname $2`/`basename $2 .bib`";
137                  fi
138                  EXTRA="${EXTRA}${DOLLARTWO},";
139                  EXTRABIB="${EXTRABIB},${DOLLARTWO}.bib";
140                  shift 2;;
141      </script>
```

- **-es** or **--extras**: if, for some reason, including extra files twice is not possible, this options provides a way of including extra **.bib** files only before the main **.bib** file(s).

```

142      <*script>
143          -es|--extras)
144              ## - extra input files (containing strings)
145              ## - will be included *before* the main files (hence not suitable
146              ## for crossrefs)
147                  opttoolate;
148                  if [ `dirname $2` = "." ]; then
149                      DOLLARTWO="`basename $2 .bib`";
150                  else
151                      DOLLARTWO="`dirname $2`/`basename $2 .bib`";
152                  fi
153                  EXTRA="${EXTRA}${DOLLARTWO},";
154                  shift 2;;
```

```

155      </script>
• -ec or --extrac: similar to the previous one, but for file(s) included after
the main .bib file(s).

```

```

156      <*script>
157          -ec|--extrac)
158              ## - extra input files (containing crossrefs)
159              ## - will be included only *after* the main files (hence not
160              ##   suitable for @string's)
161                  opttoolate;
162                  if [ "'dirname $2'" = "." ]; then
163                      DOLLARTWO="'basename $2 .bib'";
164                  else
165                      DOLLARTWO="'dirname $2'/'basename $2 .bib'";
166                  fi
167                  EXTRABIB="${EXTRABIB}, ${DOLLARTWO}.bib";
168                  shift 2;;
169      </script>

```

- -o or --output: the name of the output file.

```

170      <*script>
171          -o|--output-file)
172              ## - name of the output file
173              ## - we force it to end with '.bib'
174                  opttoolate;
175                  if [ "'dirname $2'" = "." ]; then
176                      DOLLARTWO="'basename $2 .bib'";
177                  else
178                      DOLLARTWO="'dirname $2'/'basename $2 .bib'";
179                  fi
180                  OUTPUT="${DOLLARTWO}.bib";
181                  shift 2 ;;
182      </script>

```

- -c or --crossref (or others): this option means that we want crossrefs to be included. Note that for any entry, field inheritance will be performed.

```

183      <*script>
184          -c|--crossref|--crossrefs|--with-crossref|--with-crossrefs)
185              ## - whether or not to preserve 'crossref' keys.
186              ## - by default, they are removed, but crossref'd entries are
187              ##   included.
188              ## - crossrefs are *always* expanded anyway.
189                  opttoolate;
190                  CREF="1" ;
191                  shift ;;
192      </script>

```

- -n or --no-crossref: don't include crossref'd entries.

```

193      <!*script>
194          -n|--no-crossref|--without-crossref|--no-crossrefs|--without-crossrefs)
195          ## - to remove crossref'd entries (hence remove 'crossref' keys).
196          opttoolate;
197          CREF="20000" ;
198          shift ;
199      </script>

```

- **-r** or **--replace**: this provides a way of replacing the .bib files given by \bibdata in the .aux file with (a) new one(s).

```

200      <!*script>
201          -r|--replace)
202              ## - to replace the file(s) given in \bibdata in the .aux file with
203              ## (a) new one(s).
204              opttoolate;
205              REPLACEBIB="1";
206              if [ `dirname $2` = `.` ]; then
207                  DOLLARTWO=`basename $2 .bib`;
208              else
209                  DOLLARTWO=`dirname $2`/`basename $2 .bib`;
210              fi
211              NEWBIB="${NEWBIB}${DOLLARTWO}.bib,";
212              shift 2;;
213      </script>

```

- **-v** or **--version** for version number:

```

214      <!*script>
215          -v|--version)
216              echo "This is bibexport v${VERSION} (released ${VDATE}); exit 0;;
217      </script>

```

- **-p** or **--preamble** for inserting some informations at the beginning of the output file:

```

218      <!*script>
219          -p|--preamble|--with-preamble)
220              BANNER="true";
221              shift ;
222      </script>

```

- **-t** or **--terse** for asking BibTeX to run silently:

```

223      <!*script>
224          -t|--terse|--silent)
225              TERSE="-terse ";
226              shift ;
227      </script>

```

- other dash-options are erroneous (except **-h**, but...):

```

228      <!*script>
229          -*)
230              usage;;
231      </script>

```

- there should only remain file names: we add those names to the list of files.

```

232      <!*script>
233          *)
234      ## - list of input files
235      ## - we ensure that no extra option is given later...
236      TOOLATE="1";
237      if [ `dirname $1` = "." ]; then
238          DOLLARONE=`basename $1 ${EXT}`;
239      else
240          DOLLARONE=`dirname $1`/`basename $1 ${EXT}`;
241      fi
242      FILE="${FILE}${SPACE}${DOLLARONE}${EXT}";
243      if [ ${ALL} -eq 1 ]; then
244          SPACE=",";
245      else
246          SPACE=" ";
247      fi;
248      shift;;
249      </script>

```

That's all folks:

```

250 <!*script>
251     esac
252 done
253 </script>

```

2.1.3 The core of the script

We first set the name of the result and intermediary files:

```

254 <!*script>
255 FINALFILE=${OUTPUT};
256 if [ ! "${FINALFILE}" ]; then
257     FINALFILE="bibexport.bib";
258 fi
259 TMPFILE="bibexp.`date +%s`";
260 </script>

```

We then create the .aux file for the main run of Bib_{TEX}. Note that this could call Bib_{TEX}, with the `expkeys.bst` file, in the case where we want to export all entries of a .bib file but not crossrefs. Note how, in that case, we trick Bib_{TEX} for inputting extra files twice: we include them with their short name first (with no extension), and then with the full name. We *need* to do that, since `string` abbreviations must be defined first, while crossrefs must occur after having been referenced.

```

261 <script>
262 if [ -z "${EXT}" ]; then ## we export all entries
263     if [ -z "${EXTRA}" ]; then ## we have no extra files
264         cat > ${TMPFILE}.aux <<EOF
265 \citation{*}
266 \bibdata{$FILE}
267 \bibstyle{$BST}
268 EOF
269     else ## we have extra files (e.g. for crossrefs) but want all entries from ${FILE}
270     ## we first extract the keys to be used:
271         cat > ${TMPFILE}.aux <<EOF
272 \citation{*}
273 \bibdata{$FILE}
274 \bibstyle{expkeys}
275 EOF
276     ## This run may generate errors. We redirect the output:
277     bibtex -min-crossrefs=${CREF} -terse ${TMPFILE} >/dev/null 2>&1;
278     mv -f ${TMPFILE}.bb1 ${TMPFILE}.aux;
279     ## and then prepare the .aux file for exporting:
280     cat >> ${TMPFILE}.aux <<EOF
281 \bibdata{$EXTRA}${FILE}${EXTRABIB}
282 \bibstyle{$BST}
283 EOF
284 fi
285 else ## we only export entries listed in the given .aux file:
286 if [ ! "x${REPLACEBIB}" = "x1" ]; then
287     cat ${FILE} | sed -e "s/bibstyle{.*}/bibstyle{$BST}://" > ${TMPFILE}.aux;
288 else
289     cat ${FILE} | sed -e "s/bibstyle{.*}/bibstyle{$BST}://" \
290         -e "s/bibdata{.*}/bibdata{$EXTRA}${NEWBIB%,}${EXTRABIB}://" > ${TMPFILE}.aux;
291 fi
292 fi
293 </script>

```

This was the hard part. We now call BibTeX, clean and rename the output file, and remove intermediary files:

```

294 <script>
295 if [ -z "$DEBUG" ]; then
296     bibtex -min-crossrefs=${CREF} ${TERSE} ${TMPFILE};
297     if [ -e ${FINALFILE} ]; then
298 mv ${FINALFILE} ${FINALFILE}-save-'date "+%Y.%m.%d:%H.%M.%S"'
299     fi
300     echo "" > ${FINALFILE}
301 else
302     echo "bibtex -min-crossrefs=${CREF} ${TERSE} ${TMPFILE};"
303 fi
304 if [ ! "${BANNER}" = "false" ]; then
305     ## list of cited entries
306     if [ -z "$DEBUG" ]; then
307 sed -i -e "s/\\\\bibstyle{.*}/\\\\bibstyle{expkeys}/" ${TMPFILE}.aux

```

```

308 mv ${TMPFILE}.aux ${TMPFILE}-cites.aux
309 bibtex -terse -min-crossrefs=${CREF} ${TMPFILE}-cites
310 echo -ne "@comment{generated using bibexport:\n" >> ${FINALFILE};
311 echo -ne " creation date:\t`date +\%c`\n" >> ${FINALFILE};
312 echo -ne " command:\t`basename $0` ${ARGS}\n" >> ${FINALFILE};
313 if [ -z "${EXT}" ]; then
314     echo -ne " source files:\t\t${FILETAB}\t\t\t\t${EXTRABIBTAB}\n" >> ${FINALFILE}; \
315 fi
316 cat ${TMPFILE}-cites.bbl >> ${FINALFILE};
317 echo -ne " bibexport-version:\t`$VERSION` ($VDATE)\n" >> ${FINALFILE};
318 echo -ne " bibexport-maintainer:\tmarkey(at)lsv.ens-cachan.fr\n" >> ${FINALFILE};
319 sed -i -e "s/}//g" ${FINALFILE};
320 echo -n -e "}\n\n" >> ${FINALFILE};
321 rm -f ${TMPFILE}-cites.bbl ${TMPFILE}-cites.aux ${TMPFILE}-cites.blg
322     fi
323 fi
324 if [ ${CREF} -ne 1 ]; then
325     if [ -z "$DEBUG" ]; then
326         egrep -iv '^ *crossref *= *[^,]+,?' \
327             ${TMPFILE}.bbl >> ${FINALFILE};
328     else
329         echo "egrep -iv '^ *crossref *= *[^,]+,?' ${TMPFILE}.bbl >> ${FINALFILE};"
330     fi
331 else
332     if [ -z "$DEBUG" ]; then
333         cat ${TMPFILE}.bbl >> ${FINALFILE};
334     else
335         echo "cat ${TMPFILE}.bbl >> ${FINALFILE};"
336     fi
337 fi
338 if [ -z "$DEBUG" ]; then
339     rm -f ${TMPFILE}.bbl ${TMPFILE}.aux ${TMPFILE}.blg;
340 else
341     echo "rm -f ${TMPFILE}.bbl ${TMPFILE}.aux ${TMPFILE}.blg";
342 fi
343 
```

2.2 The `expkeys.bst` file

The only role of that file is to export the list of entries to be exported. It is used when we export all the entries of `.bib` files, except those of *extra* `.bib` files. Thus:

```

344 (*expkeys)
345 ENTRY{}{}{}
346 READ
347 FUNCTION{export.key}
348 {
349     "\citation{" cite$ "}" * * write$ newline$
350 }
351 ITERATE{export.key}

```

```
352 ⟨/expkeys⟩
```

2.3 The **expcites.bst** file

This file is used for exporting and formating the list of \cited entries. We begin with some parameters defining the margins

2.3.1 Some configuration values

```
left.width
right.width 353 ⟨*expcites⟩
url.right.width 354 FUNCTION{left.width}{#23}
left.short.width 355 FUNCTION{right.width}{#55}
right.short.width 356 FUNCTION{url.right.width}{#61}
left.delim 357 FUNCTION{left.short.width}{#10} %% for @preamble
right.delim 358 FUNCTION{right.long.width}{#63}
359 FUNCTION{left.delim}{quote$}
360 FUNCTION{right.delim}{quote$}
361 ⟨/expcites⟩
```

2.3.2 Entries

We only want to export \cited keys, so we won't use any field.

```
ENTRY
```

```
362 ⟨*expcites⟩
363 ENTRY{dummy}{}{}
364 ⟨/expcites⟩
```

2.3.3 Basic functions

```
or
and 365 ⟨*expcites⟩
not 366 FUNCTION{not}
367 {
368   {#0}
369   {#1}
370   if$
371 }
372 FUNCTION{and}
373 {
374   'skip$'
375   {pop$ #0}
376   if$
377 }
378 FUNCTION{or}
379 {
380   {pop$ #1}
381   'skip$'
```

```

382   if$
383 }
384 </expctes>

```

2.3.4 Splitting strings

We design functions for splitting strings, so that the final .bib file will be cleanly indented.

```

space.complete
split.string 385 </expctes>
386 INTEGERS{left.length right.length}
387 STRINGS{ s t }
388 INTEGERS{bool}
389 FUNCTION{space.complete}
390 {
391   'left.length :=
392   duplicate$ text.length$ left.length swap$ -
393   {duplicate$ #0 >}
394   {
395     swap$ " " * swap$ #1 -
396   }
397   while$
398   pop$
399 }
400 FUNCTION{split.string}
401 {
402   'right.length :=
403   duplicate$ right.length #1 + #1 substring$ "" =
404   {"}
405   {
406     's :=
407     right.length
408     {duplicate$ duplicate$ s swap$ #1 substring$ " " = not and}
409     {#1 -}
410     while$
411     duplicate$ #2 <
412     {
413       pop$ " " s * ""
414     }
415     {
416       duplicate$ s swap$ #1 swap$ substring$ swap$
417       s swap$ global.max$ substring$ swap$
418     }
419   }
420   if$
421 }
422 if$
423 }
424 </expctes>

```

2.3.5 Exporting cited entries

Now we initialize, and export \cited entries.

```
init.cited.keys
write.cited.keys 425 {*expctes}
write.cited.keys.last 426 FUNCTION{init.cited.keys}
    cited.keys 427 {
end.cited.keys 428     left.delim 's :=
429     #0 'bool :=
430 }
431 FUNCTION{write.cited.keys}
432 {
    bool
434     {" left.width space.complete swap$}
435     {" cited keys: " left.width space.complete swap$"
436         #1 'bool :=}
437     if$
438     {duplicate$ text.length$ right.width >}
439     {
440         right.width split.string 't :=
441         *
442         write$ newline$
443         "" left.width space.complete t
444     }
445     while$
446     pop$ pop$ t
447 }
448 FUNCTION{write.cited.keys.last}
449 {
    bool
450     {" left.width space.complete swap$}
451     {" cited keys: " left.width space.complete swap$"
452         #1 'bool :=}
453     if$
454     {duplicate$ duplicate$ text.length$ #1 substring$ "," = not}
455     {duplicate$ text.length$ #1 - #1 swap$ substring$}
456     while$
457     duplicate$ text.length$ #1 - #1 swap$ substring$
458     right.delim *
459     {duplicate$ "" = not}
460     {
461         *
462         right.width split.string 't :=
463         *
464         write$ newline$
465         "" left.width space.complete t
466     }
467     while$
468     pop$ pop$
469 }
```

```

470 FUNCTION{cited.keys}
471 {
472   s cite$ ", " * * 's :=
473   s text.length$ #4000 >
474     {s write.cited.keys 's :=}
475     'skip$
476   if$
477 }
478 FUNCTION{end.cited.keys}
479 {
480   s write.cited.keys.last
481 }
482 
```

2.3.6 Now, we export...

We now export everything...

```

483 <*expcties>
484 FUNCTION{article}{cited.keys}
485 FUNCTION{book}{cited.keys}
486 FUNCTION{booklet}{cited.keys}
487 FUNCTION{conference}{cited.keys}
488 FUNCTION{habthesis}{cited.keys}
489 FUNCTION{inbook}{cited.keys}
490 FUNCTION{incollection}{cited.keys}
491 FUNCTION{inproceedings}{cited.keys}
492 FUNCTION{journals}{cited.keys}
493 FUNCTION{manual}{cited.keys}
494 FUNCTION{mastersthesis}{cited.keys}
495 FUNCTION{misc}{cited.keys}
496 FUNCTION{phdthesis}{cited.keys}
497 FUNCTION{proceedings}{cited.keys}
498 FUNCTION{techreport}{cited.keys}
499 FUNCTION{unpublished}{cited.keys}
500 READ
501 EXECUTE{init.cited.keys}
502 ITERATE{cited.keys}
503 EXECUTE{end.cited.keys}
504 
```

2.4 The **export.bst** file

2.4.1 Some configuration values

<code>left.width</code>	We define here the indentation values, and the field delimiters. <i>short width</i> are used for <code>@preamble</code> .
<code>right.width</code>	
<code>url.right.width</code>	505 <*export>
<code>left.short.width</code>	506 FUNCTION{left.width}{#18}
<code>right.short.width</code>	507 FUNCTION{right.width}{#55}
<code>left.delim</code>	
<code>right.delim</code>	

```

508 FUNCTION{url.right.width}{#61}
509 FUNCTION{left.short.width}{#10} %% for @preamble
510 FUNCTION{right.long.width}{#63}
511 FUNCTION{left.delim}{""}
512 FUNCTION{right.delim}{""}
513 %FUNCTION{left.delim}{quote$}
514 %FUNCTION{right.delim}{quote$}
515 (/export)

```

2.4.2 Entries

We use standard entries here. Of course, more entries could be added for special .bib files. Those extra entries will also have to be added in the main exporting function.

ENTRY

```

516 (*export)
517 ENTRY{
518 % Standard fields:
519   address
520   author
521   booktitle
522   chapter
523   edition
524   editor
525   howpublished
526   institution
527   journal
528   key
529   month
530   note
531   number
532   organization
533   pages
534   publisher
535   school
536   series
537   title
538   type
539   volume
540   year
541 % Special (but still somewhat standard) fields (natbib, germbib, ...):
542   abstract
543   doi
544   eid
545   isbn
546   issn
547   language
548   url
549 }{}{}

```

```
550 ⟨/export⟩
```

2.4.3 Basic functions

No comment.

```
or
and 551 ⟨*export⟩
not 552 FUNCTION{not}
553 {
554     {#0}
555     {#1}
556     if$
557 }
558 FUNCTION{and}
559 {
560     'skip$'
561     {pop$ #0}
562     if$
563 }
564 FUNCTION{or}
565 {
566     {pop$ #1}
567     'skip$'
568     if$
569 }
570 ⟨/export⟩
```

2.4.4 Splitting strings

We design functions for splitting strings, so that the final .bib file will be cleanly indented.

```
space.complete
split.string 571 ⟨*export⟩
split.url 572 INTEGERS{left.length right.length}
split.name 573 STRINGS{ s t }
574 FUNCTION{space.complete}
575 {
576     'left.length :=
577     duplicate$ text.length$ left.length swap$ -
578     {duplicate$ #0 >}
579     {
580         swap$ " " * swap$ #1 -
581     }
582     while$
583     pop$
584 }
585 FUNCTION{split.string}
586 {
```

```

587   'right.length :=
588   duplicate$ right.length #1 + #1 substring$ "" =
589   {""}
590   {
591     's :=
592     right.length
593     {duplicate$ duplicate$ s swap$ #1 substring$ " " = not and}
594     {#1 -}
595     while$
596     duplicate$ #2 <
597     {
598       pop$ "    " s * ""
599     }
600     {
601       duplicate$ s swap$ #1 swap$ substring$
602       swap$
603       s swap$ global.max$ substring$
604     }
605     if$
606   }
607   if$
608 }
609 FUNCTION{split.url}
610 {
611   'right.length :=
612   duplicate$ right.length #1 + #1 substring$ "" =
613   {""}
614   {
615     's :=
616     right.length
617     {duplicate$ duplicate$ s swap$ #1 substring$ "/" = not and}
618     {#1 -}
619     while$
620     duplicate$ #2 <
621     {
622       pop$ "    " s * ""
623     }
624     {
625       duplicate$ s swap$ #1 swap$ substring$
626       swap$ #1 +
627       s swap$ global.max$ substring$
628     }
629     if$
630   }
631   if$
632 }
633 FUNCTION{split.name}
634 {
635   'right.length :=
636   duplicate$ right.length #1 + #1 substring$ "" =

```

```

637      {""}
638      {
639          's := 
640          right.length
641          {duplicate$ duplicate$ s swap$ #5 substring$ " and " = not and}
642          {#1 -}
643          while$
644          duplicate$ #2 <
645          {
646              pop$ " " s * ""
647          }
648          {
649              #4 + duplicate$ s swap$ #1 swap$ substring$ 
650              swap$ 
651              s swap$ global.max$ substring$ 
652          }
653          if$
654      }
655      if$
656 }
657 </export>

```

2.4.5 Exporting fields

Here, we have four exporting functions, since we also have to deal with abbreviations:

```

field.export
abbrv.export 658 (*export)
name.export 659 FUNCTION{field.export}
url.export 660 {
    661     duplicate$ missing$
    662     'skip$ 
    663     {
    664         left.delim swap$ * right.delim *
    665         swap$ 
    666         " " swap$ * " = " * left.width space.complete
    667         swap$ ","
    668         {duplicate$ "" = not}
    669         {
    670             right.width split.string 't :=
    671             *
    672             write$ newline$
    673             "" left.width space.complete t
    674         }
    675         while$
    676     }
    677     if$
    678     pop$ pop$
679 }

```

```

680 FUNCTION{abbrv.export}
681 {
682   duplicate$ missing$
683   'skip$'
684   {
685     swap$'
686     " " swap$ * " = " * left.width space.complete
687     swap$ "," *
688     {duplicate$ "" = not}
689     {
690       right.width split.string 't :=*
691       *
692       write$ newline$
693       "" left.width space.complete t
694     }
695     while$'
696   }
697   if$'
698   pop$ pop$'
699 }
700 FUNCTION{name.export}
701 {
702   duplicate$ missing$'
703   'skip$'
704   {
705     left.delim swap$ * right.delim *
706     swap$'
707     " " swap$ * " = " * left.width space.complete
708     swap$ "," *
709     {duplicate$ "" = not}
710     {
711       right.width split.name 't :=*
712       *
713       write$ newline$
714       "" left.width space.complete t
715     }
716     while$'
717   }
718   if$'
719   pop$ pop$'
720 }
721 FUNCTION{url.export}
722 {
723   duplicate$ missing$'
724   'skip$'
725   {
726     left.delim swap$ * right.delim *
727     swap$'
728     " " swap$ * " = " * left.width space.complete
729     swap$ "," *

```

```

730     {duplicate$ "" = not}
731     {
732         url.right.width split.url 't :=
733         *
734         write$ newline$
735         "" left.width space.complete t
736     }
737     while$ 
738 }
739 if$
740 pop$ pop$
741 }
742 </export>

```

2.4.6 Handling abbreviations

Abbreviations are difficult to deal with if we wish to still use them, since BibTeX will expand them before we can do anything. All we can do is to define them in a special way, in order to be able to get back to the abbreviations later on. This is precisely what we do:

```

jan-dec
acmcs-tcs 743 <*export>
remove.exports.from.months 744 MACRO{jan}{ "export-jan" }
remove.export.from.journal 745 MACRO{feb}{ "export-feb" }
746 MACRO{mar}{ "export-mar" }
747 MACRO{apr}{ "export-apr" }
748 MACRO{may}{ "export-may" }
749 MACRO{jun}{ "export-jun" }
750 MACRO{jul}{ "export-jul" }
751 MACRO{aug}{ "export-aug" }
752 MACRO{sep}{ "export-sep" }
753 MACRO{oct}{ "export-oct" }
754 MACRO{nov}{ "export-nov" }
755 MACRO{dec}{ "export-dec" }
756 MACRO{acmcs}{ "export-acmcs" }
757 MACRO{acta}{ "export-acta" }
758 MACRO{cacm}{ "export-cacm" }
759 MACRO{ibmjrd}{ "export-ibmjrd" }
760 MACRO{ibmsj}{ "export-ibmsj" }
761 MACRO{ieeese}{ "export-ieeese" }
762 MACRO{ieeetc}{ "export-ieeetc" }
763 MACRO{ieeetcad}{ "export-ieeetcad" }
764 MACRO{ipl}{ "export-ipl" }
765 MACRO{jacm}{ "export-jacm" }
766 MACRO{jcss}{ "export-jcss" }
767 MACRO{scp}{ "export-scp" }
768 MACRO{sicomp}{ "export-sicomp" }
769 MACRO{tocss}{ "export-tocs" }
770 MACRO{todss}{ "export-tods" }

```

```

771 MACRO{togs}{ "export-tog" }
772 MACRO{toms}{ "export-toms" }
773 MACRO{toois}{ "export-poois" }
774 MACRO{toplas}{ "export-toplas" }
775 MACRO{tcs}{ "export-tcs" }
776 INTEGERS{ intxt }
777 FUNCTION{remove.exports.from.months}
778 {
779   #0 'intxt :=
780   duplicate$ missing$
781   'skip$
782   {'t :=
783   ""
784   {t #1 #1 substring$ "" = not}
785   {
786     t #1 #7 substring$ "export-" =
787     {intxt
788       {right.delim * #0 'intxt :=}
789       'skip$
790       if$
791       duplicate$ "" =
792         'skip$
793         {" # " *}
794       if$
795       t #8 #3 substring$ *
796       t #11 global.max$ substring$ 't :=}
797     {intxt
798       'skip$
799       {duplicate$ "" =
800         {}
801         {" # " *}
802       if$
803         left.delim * #1 'intxt :=}
804     if$
805     t #1 #1 substring$ *
806     t #2 global.max$ substring$ 't :=}
807   if$
808   }
809   while$
810   intxt
811   {right.delim *}
812   'skip$
813   if$
814   }
815   if$
816 }
817 FUNCTION{remove.export.from.journals}
818 {
819   duplicate$ missing$
820   'skip$
```

```

821      {
822        duplicate$ #1 #7 substring$ "export-" =
823          {#8 global.max$ substring$}
824          {left.delim swap$
825            right.delim **}
826        if$
827      }
828    if$
829  }
830 </export>

```

2.4.7 Now, we export...

We gather everything. This is were special fields must be added for being exported:

```

entry.export.standard
entry.export.extra 831 (*export)
entry.export 832 FUNCTION{entry.export.standard}
  export 833 {
    834   "address" address field.export
    835   "author" author name.export
    836   "booktitle" booktitle field.export
    837   "chapter" chapter field.export
    838   "crossref" crossref field.export
    839   "edition" edition field.export
    840   "editor" editor name.export
    841   "howpublished" howpublished field.export
    842   "institution" institution field.export
    843   "journal" journal remove.export.from.journals abbrv.export
    844   "key" key field.export
    845   "month" month remove.exports.from.months abbrv.export
    846   "note" note field.export
    847   "number" number field.export
    848   "organization" organization field.export
    849   "pages" pages field.export
    850   "publisher" publisher field.export
    851   "school" school field.export
    852   "series" series field.export
    853   "type" type field.export
    854   "title" title field.export
    855   "volume" volume field.export
    856   "year" year field.export
  857 }
  858 FUNCTION{entry.export.extra}
  859 {
    860   "abstract" abstract field.export
    861   "doi" doi field.export
    862   "eid" eid field.export
    863   "isbn" isbn field.export
    864   "issn" issn field.export

```

```

865 "language" language field.export
866 "url" url url.export
867 }
868 FUNCTION{entry.export}
869 {
870 entry.export.standard
871 entry.export.extra
872 }
873 FUNCTION{export}
874 {
875 "@" type$ * "{" * cite$ * "," * write$ newline$
876 entry.export
877 "}" write$ newline$ newline$
878 }
879 </export>

```

2.4.8 Miscellanea

We also have to handle preamble, and to define functions for each entry type (we won't use them but otherwise, BibTeX would complain).

```

preamble
  header 880 <*export>
entries.headers 881 FUNCTION{preamble}
article-unpublished 882 {
  883 preamble$ duplicate$ "" =
  884   'pop$
  885   {
    886     ",-----." write$ newline$
    887     "| PREAMBLE |" write$ newline$
    888     "'-----'" write$ newline$ newline$
    889     "@preamble{ " swap$
    890     quote$ swap$ * quote$ *
    891     {duplicate$ "" = not}
    892     {
      893       right.long.width split.string 't :=
      894       *
      895       write$ newline$
      896       "" left.short.width space.complete t
    897     }
    898     while$
    899     "}" write$ newline$ newline$
    900     pop$ pop$
  901   }
  902 if$
  903 }
904 FUNCTION{header}
905 {
906 %"** This file has been automatically generated by bibexport **"
907 %write$ newline$
```

```

908 %"** See    http://www.lsv.ens-cachan.fr/~markey/bibla.php      **"
909 %write$ newline$
910 %"** for more informations about bibexport.                      **"
911 %write$ newline$
912 newline$
913 }
914 FUNCTION{entries.header}
915 {
916 preamble$ "" =
917   'skip$
918   {
919     ",-----." write$ newline$
920     "| BIBTEX ENTRIES |" write$ newline$
921     "-----'" write$ newline$ newline$
922   }
923 if$
924 }
925 FUNCTION{article}{export}
926 FUNCTION{book}{export}
927 FUNCTION{booklet}{export}
928 FUNCTION{conference}{export}
929 FUNCTION{habthesis}{export}
930 FUNCTION{inbook}{export}
931 FUNCTION{incollection}{export}
932 FUNCTION{inproceedings}{export}
933 FUNCTION{journals}{export}
934 FUNCTION{manual}{export}
935 FUNCTION{mastersthesis}{export}
936 FUNCTION{misc}{export}
937 FUNCTION{phdthesis}{export}
938 FUNCTION{proceedings}{export}
939 FUNCTION{techreport}{export}
940 FUNCTION{unpublished}{export}
941 </export>

```

2.4.9 Main program

We now can execute and iterate those functions:

```

942 <*export>
943 READ
944 EXECUTE{header}
945 EXECUTE{preamble}
946 EXECUTE{entries.header}
947 ITERATE{export}
948 </export>

```